

REV	Content of Amendment	Update

RoHS

## Fiber Optical Patch Cord, LC-ST, SM Duplex, PVC or LSZH, OD=2.0x4.1 or 2.8x5.7(mm)



① ② ③

④

### Features

Standard: Telcordia GR-326-CORE  
 UPC or APC polishing  
 Single mode fiber: ITU- TG.652, G655, G657  
 Standard housing, ceramic ferrule  
 Cable diameter: 2.0x4.1 or 2.8x5.7(mm)  
 Fiber type: 9/125  $\mu$ m,  
 Insertion loss: SM Less than 0.3dB  
 Return loss: UPC SM larger than 55dB  
                   PC SM larger than 50 dB  
 Repeatability: Less than 0.2 dB  
 Changeability: Less than 0.1 dB  
 Operating temperature range: -40 $^{\circ}$ c ~ 80 $^{\circ}$ c  
 Storage temperature range: -40 $^{\circ}$ c ~ 80 $^{\circ}$ c  
 Tensile strength: 100N  
 Min. bending radius: 35mm  
 RoHS compliance

No.	Description	Qty
①	T cap	4
②	Clip	1
③	Boot	4
④	Optical Cable	1

UNIT	mm	PN: XXM-LC/ST-SD					
DATE	03/27/12						
DRAW							
CHECK							
APP. D		SCALE	SIZE	A4	PAGE	REV	A