



CAT 8.1 40G CMR S/FTP Solid Dual Shielded Bulk Cable

Our Category 8.1 40G (S/FTP) high performance data communications cable is ideal for a large data driven network installation. This cable is designed for short runs indoor up to 30 Meters in length. Our Category 8.1 cable has 4 pairs of 23AWG solid bare copper conductors, individually shielded pairs with an overall TC braiding. This cable has a CMR Riser fire rating and supplied on a 500ft & 1000ft wooden spool, which is marked in descending order so you always know how much cable is left.

Applications

- 25/40GBASE-T
- Rackcenters Topologies Supported:
- Top-of-Rack (ToR)
- End-of-Row (EoR)
- Middle-of-Row (MoR)

Compliance

- CAT8 Version 8.1
- ISO/IEC 11801;IEC61156, YD/T1019
- TIA/EIA-568-C.2-1 Category 8.1
- RoHS Compliance For The Requirement Of European Union Issued Directive 2002/95/EC


Physical Characteristics

- Conductor Size: 23 AWG
- Conductor Material: Solid Bare Copper
- Insulation Material: Foam Polyethylene
- Insulation Diameter: 1.37 mm
- Number Of Conductors: 8 Conductors / 4 Pairs
- Inner Pair Shielding: AL/Mylar
- Outer Shield Material: TC Braiding
- TC Braiding Coverage: 60%
- Outer Jacket Diameter: 7.8mm
- Outer Jacket Rip Cord: No
- Outer Jacket Material: PVC

CAT 8.1



Technical Diagram



Available Jacket Colors

- Blue Item# C8SS-7006RB 500ft Length
- Blue Item# C8SS-7005RB 1000ft Length



Cable Features

- Meets Or Exceeds CAT 8.1 T568-C.2-1 Standards
- Outer Jacket is CMR Fire Rated
- Easy To Use Wooden Spool
- Extra Headroom Provides Room For Growth
- Low Attenuation And Power-Sum Crosstalk

Construction Facts

- Cable Has High Density Polyethylene Insulation
- AL Shielding Is Used To Help Eliminate Interference

Cable Put-Ups:

Cable is supplied in 500ft and 1000ft increments on a wooden spool.

CAT 8.2 40Gig Solid Bulk Cable Electrical Specifications

Frequency MHz (Maximum)	ATT dB/30 m (98.4 ft.) (Maximum)	ACRF dB/30 m (98.4 ft.) (Maximum)	PSACRF dB/30 m (98.4 ft.) (Maximum)	NEXT dB/30 m (98.4 ft.) (Minimum)	PS-NEXT dB/30 m (98.4 ft.) (Minimum)	ELFEXT dB/30 m (98.4 ft.) (Minimum)	PS-ELFEXT dB/30 m (98.4 ft.) (Minimum)	Return Loss dB (Minimum)
1.0	3.0	65.0	62.0	65.0	62.0	N/A	N/A	19.0
4.0	3.0	59.9	56.9	63.8	60.5	N/A	N/A	19.0
8.0	3.0	53.9	50.9	58.9	55.6	N/A	N/A	19.0
10.0	3.0	52.0	49.0	57.3	54.0	N/A	N/A	19.0
16.0	3.0	47.9	44.9	53.9	50.6	N/A	N/A	18.0
20.0	3.0	45.9	42.9	52.3	49.0	N/A	N/A	17.5
25	3.2	44.0	41.0	50.7	47.3	N/A	N/A	17.0
31.25	3.6	42.1	39.1	49.1	45.7	N/A	N/A	16.5
62.5	5.1	36.0	33.0	44.0	40.6	N/A	N/A	16.0
100	6.5	32.0	29.0	40.5	37.1	N/A	N/A	16.0
200	9.3	25.9	22.9	35.3	31.9	N/A	N/A	14.3
250	10.4	24.0	21.0	33.6	30.2	N/A	N/A	13.4
300	11.5	22.4	19.4	32.3	28.8	N/A	N/A	12.7
400	13.3	19.9	16.9	30.1	26.6	N/A	N/A	11.6
500	15.0	18.0	15.0	27.9	24.8	N/A	N/A	10.7

PrimusCable.com - (951) 824-1571



CAT 8.1 40G CMR S/FTP Solid Dual Shielded Bulk Cable

CAT 8.2 40Gig Solid Bulk Cable Electrical Specifications

Frequency MHz (Maximum)	ATT dB/30 m (98.4 ft.) (Maximum)	ACRF dB/30 m (98.4 ft.) (Maximum)	DELAY ns/30 m (98.4 ft.) (Minimum)	NEXT dB/30 m (98.4 ft.) (Minimum)	PS-NEXT dB/30 m (98.4 ft.) (Minimum)	ELFEXT dB/30 m (98.4 ft.) (Minimum)	PS-ELFEXT dB/30 m (98.4 ft.) (Minimum)	Return Loss dB (Minimum)
600	16.5	16.4	13.4	25.7	22.7	N/A	N/A	10.0
1000	22.0	12.0	9.0	19.3	16.5	N/A	N/A	8.0
1500	27.7	8.4	5.4	13.9	11.2	N/A	N/A	8.0
2000	32.7	5.9	2.9	9.8	7.3	N/A	N/A	8.0

Pair Color Code Chart

- Pair 1 — White/Blue Stripe & Blue
- Pair 2 — White/Orange Stripe & Orange
- Pair 3 — White/Green Stripe & Green
- Pair 4 — White/Brown Stripe & Brown

Mechanical Characteristics

- Installation Temperature Range: 0°C-60°C
- Operating Temperature Range: -20°C-75°C
- Storage Temperature Range: -20°C-75°C
- Bulk Cable Weight:
 - 28 lbs./ 500FT
 - 54 lbs./ 1000FT
- Max. Recommended Pulling Tension: 400N
- Min. Bend Radius/Minor Axis: 10xOD
- Min. Bend/Installation: 8xOD
- Test Object: Jacket
- Before Tensile Strength: ≥10.0 Mpa
 - Aging Elongation: ≥125%
 - Aging Condition: 100°C x 24hrs x 7Days
- After Tensile Strength: ≥8.0
 - Aging Elongation: ≥100%
 - Cold Bend: No Visible Cracks (-20°±2°x4h)

Electrical Characteristics

- Unbalanced to Ground Capacitance Max: 99 (pF/30m)
- Nominal Velocity of Propagation: 78%
- Maximum Delay: N/A
- Maximum Delay Skew: N/A
- Maximum Conductor DC Resistance: 67.9 (20°C ohmm/km)
- Maximum Operating Voltage - UL: N/A
- Maximum DCR Unbalanced: 5% (@ 20°C)
- Attenuation (Maximum)
 - 16.5dB/30m (98.4 ft.) @ 600MHz
 - 32.7dB/30m (98.4 ft.) @ 2000MHz
- NEXT (Minimum)
 - 25.7dB/30m (98.4 ft.) @ 600MHz
 - 9.8dB/30m (98.4 ft.) @ 2000MHz
- Return Loss (Minimum)
 - 10.0dB/30m (98.4 ft.) @ 600MHz
 - 8.0dB/30m (98.4 ft.) @ 2000MHz

©2018 CRN Solutions Inc. dba. Primus Cable
All Rights Reserved.

Although Primus Cable makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Primus Cable provides the information and specifications herein on an “AS IS” basis, with no representations or warranties, whether express, statutory or implied. In no event will Primus Cable be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Primus Cable has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Primus Cable products are subject to Primus Cable’s standard terms and conditions of sale.

Primus Cable believes this product to be in compliance with EU RoHS (Directive 2002/EC, 27 Jan 2003). Material manufactured prior to the compliance date may be in stock at Primus Cable facilities and in our Distributor’s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Primus Cable’s knowledge, information, and belief at the date any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification and regulations based on their individual usage of the product.

Primus Cable declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC

